



APS Automotive Enterprises Co.,Ltd.

A2,2ND Floor,Main Building,33 Changhong Road,Modern Logistics Park,Xiamen,China 361006

Tel: 86-592-5619 592 86-592-2620 070 Fax: 86-592-5610884 E-mail: aa@aaps.cn / karl@cps.cn

<http://www.apspart.com>

<http://apsparts.en.alibaba.com/index.html>

NO.	CAR	APS NO.	OEM NO	MODEL & DESCRIPTION	CYL NO.	CYL. DIA	PISTON				PIN		CLIP	N.W. (KG)
							LONG	COMP DIST	RING		DIA	LONG		
									COMP	OIL				
1	HOLDEN	APS 27801	7430511	186 C.R 9.2T01	6	92.075 3.625"	79.883 3.145"	45.313 1.784"	2-5/64"	1-3/16"	22	69.05		0.495
2	HOLDEN	APS 27801A		AFM6186P	6	92.075 3.625"	79.883 3.145"	45.313 1.784"	2-5/64"	1-3/16"	22	69.05		0.495
3	HOLDEN	APS 27801W	7430511	186.186SENGS C.R 9.2T01	6	92.075 3.625"	79.883 3.145"	45.313 1.784"	2-5/64"	1-3/16"	22	69.05		
4	HOLDEN	APS 27803	2819505	202 CUI NENG 3310cc CR 9.4T01	6	92.075 3.625"	76.708 3.02"	42.26-1.2 1.6638"-0.0473"	2-5/64"	1-3/16"	22	69.05		0.467
5	HOLDEN	APS 27803A		AFM16202P CR 9.4T01	6	92.075 3.625"	76.708 3.02"	42.26-1.2 1.6638"-0.0473"	2-5/64"	1-3/16"	22	69.05		0.467
6	HOLDEN	APS 27803HB	2809504	202 C.i	6	92.130 3.6272"	76.708 3.02"	42.265-1.27 1.664"-0.05"	2-5/64"	1-3/16"	22	69.29		0.517
7	HOLDEN	APS 27806	7424727	179	6	90.487 3.5625"	80.391 3.165"	45.313 1.784"	2-5/64"	1-3/16"	22	69.05		0.47
8	HOLDEN	APS 27807	2811407	308 CUI NENG C.R 9T01	8	101.6 4.0"	80.416 3.166"	42.926-4.116 1.69"-0.16205"	2-5/64"	1-3/16"	23.558	73.42		0.617
9	HOLDEN	APS 27807A		V8 308 C.i ENGINE	8	101.6	80.416	42.926-4.116	2-5/64"	1-3/16"	23.558	73.42		0.617
10	HOLDEN	APS 27808	2811402	253 CUI NENG 4616cc C.R9T01	8	92.075 3.625"	77.11 3.0359"	42.926 1.69"	2-5/64"	1-3/16"	23.558	69.05		0.493
11	HOLDEN	APS 27808A	2811402	253 CUI NENG 4616cc	6	92.075 3.625"	76.962 3.0359"	42.926 1.69"	2-5/64"	1-3/16"	23.558	69.05		0.493
12	HOLDEN	APS 27809	9937221	308	8	101.6 4.0"	80.467 3.1680"	42.926-2.667 1.69"-0.105"	2-5/64"	1-3/16"	23.558	73.42		0.631 0.460
13	HOLDEN	APS 27809A			8	101.6 4.0"	80.467 3.1680"	42.926-2.667 1.69"-0.105"	2-5/64"	1-3/16"	23.558	73.42		0.631
14	HOLDEN	APS 27810		253	8	92.075 3.625"	78.5 3.0906"	43.175+1.25 1.6998"+0.0492"	2-5/64"	1-3/16"	23.558	73.42		0.495

15	HOLDEN	APS 27811	7430518	161	6	85.725 3.375"	80.4 3.1653"	45.31 1.784"	2-5/64"	1-3/16"	22	69.05		0.462
16	HOLDEN	APS 27811A	7429481		6	85.763 3.3765"	81.026 3.190"	45.313 1.784"	2-5/64"	1-3/16"	22	69.29		0.462
17	HOLDEN	APS 27811B			6	85.725 3.375"	80.4 3.1654"	45.313 1.784"	2-5/64"	1-3/16"	22	69.05		0.439
18	HOLDEN	APS 27812		FHP6202	6	92.075 3.625"	76.2 3.0"	42.4 1.6693"	2-5/64"	1-3/16"	22	69.05		0.443
19	HOLDEN	APS 27813		FHP6186	6	92.075 3.625"	79.3 3.1221"	45.7 1.7993"	2-5/64"	1-3/16"	22	69.05		0.42
20	HOLDEN	APS 27813A		186 XUI TORANA	6	92.087 3.6255"	79.883 3.145"	45.313 1.784"	2-2.0	1-3/16"	22	69.29		
21	HOLDEN	APS 27814		PHP8308	8	101.6 4.0"	79.0 3.1103"	43.38 1.7079"	2-5/64"	1-3/16"	23.558	72.8		0.644
22	HOLDEN	APS 27814A	9934645	L34 TORANA	8	101.612 4.0005"	78.74 3.10"	43.23 1.702"	2-5/64"	1-3/16"	23.558	73.53		
23	HOLDEN	APS 27815		AFM6173P	6	88.9 3.5"	80.6 3.1773"	45.3-0.7 1.7835"-0.0276"	2-5/64"	1-3/16"	22	69.05		0.466
24	HOLDEN	APS 27815W		301	6	88.9 3.5"	80.6 3.1773"	45.3-0.7 1.7835"-0.0276"	2-5/64"	1-3/16"	22	69.05		
25	HOLDEN	APS 27816			6	77.8 3.063"	77.673 3.058"	45.212 1.780"	2-3/32"	1-3/16"	19.05	66.8	22 1.6R	0.304
26	HOLDEN	APS 27817	7420029		6	82.562 3.2505"	79.502 3.130"	45.313 1.784"	2-5/64"	1-3/16"	22	69.29		0.406
27	HOLDEN	APS 27818			6	79.387 3.1255"	77.8 3.063"	45.212 1.780"	2-5/64"	1-3/16"	19.05	66.8		0.364
28	HOLDEN	APS 27819		TORANA 1900cc	4	93.012 3.6619"	86.771 3.4162"	44.62-3.5 1.7567"-0.1378"	2-2.0	1-5.0	23	76.38		0.519
29	HOLDEN	APS 27820	3923294	307	8	98.437 3.8755"	85.394 3.362"	42.519 1.674"	2-5/64"	1-3/16"	23.558	76.45		0.598
30	HOLDEN	APS 27821	7189815		4	77.8 3.063"	75.184 2.960"	37.236 1.466"	2-5/64"	1-3/16"	20	68.65		0.352
31	HOLDEN	APS 27822			4	80.0 3.1497"	72.1 2.8386"	40.0-3.1 1.5749"-0.1221"	1-1.5 1-1.7	1-4.0	23	70.0		0.36
32	HOLDEN	APS 27822A			4	80.0 3.1497"	72.1 2.8386"	40.0-3.1 1.5749"-0.1221"	1-1.5 1-1.7	1-4.0	23	70.0		0.36
33	HOLDEN	APS 27822A1			4	80.0 3.1497"	72.1 2.8386"	40.0-3.1 1.5749"-0.1221"	1-1.5 1-1.7	1-4.0	23	70.0		0.36

34	HOLDEN	APS 27823			4	84.8	72	40.0-3.0	1-1.5 1-1.75	1-4.0	23	70.0		0.426
35	HOLDEN	APS 27824			4	84.8	72	40.0-3.5	1-1.5 1-1.75	1-4.0	23	70.0		0.405
36	HOLDEN	APS 27825			4	86	50.5	30.5-5.0	2-1.5	1-3.0	21	61.5		0.339
37	HOLDEN	APS 27826I		AFMV638	6	96.5	65.5	35.5-6.6	2-1.5	1-3.0	23	60.5		0.412
38	HOLDEN	APS 27827	RA2935		4	84.8	71.7	39.7-2.4 -5.0	1-1.5 1-1.75	1-4.0	23	70.0		0.398
39	HOLDEN	APS 27828	9203338	16LF	4	80	57.1	31.9-1.8	2-1.5	1-3.0	21	53.0		0.281